GROUND LADDER INSPECTION

Date:_____

- All ground ladders must be inspected annually or after exposure to heat, suspected of being unsafe, after being overloaded or after impact or unusual contact.
- All ground ladders must be used, inspected and maintained in accordance with the manufacturer's guidelines.

* **Manufacturer's Name**: _____ * **Mfg. SERIAL #**: _____

* **FD # or Apparatus #:** _____ * **Length:** _____

* **Ladder Type**: Single ( ) Roof ( ) Extension ( )
Folding( ) Combination ( ) Other ( ) _____

* **Construction**: Metal ( ) Wood ( ) Fiberglass ( )
Solid Beam ( ) Truss Beam ( )

***Inspect**:

Beams (burrs, sharp edges, cracks, splinters, breaks, gouges, checks, wavy conditions)	Pass ( )	Fail ( )	
Dogs/Pawl/Locks (cracks, operation, loose, damaged, lubricated)	Pass ( )	Fail ( )	N/A ( )
Rungs (snug/tight, bends, burrs, break, welds)	Pass ( )	Fail ( )	
Pulley (damaged, cracks, operational, oiled)	Pass ( )	Fail ( )	N/A ( )
Halyard/Cable (frayed rope, damaged cable/wire, knots, kinks)	Pass ( )	Fail ( )	N/A ( )
Roof Hooks (sharp, operational, deformed)	Pass ( )	Fail ( )	N/A ( )
Bolts/rivets (tight)	Pass ( )	Fail ( )	
Feet/ Butt spurs (loose, wear, damaged, operational)	Pass ( )	Fail ( )	
Welds (cracks, broken)	Pass ( )	Fail ( )	
Clean Condition	Pass ( )	Fail ( )	
Waxed/Oiled (extension ladders)	Yes ( )	No ( )	
Other: _____	Pass ( )	Fail ( )	
***Wood ladders** (cracks, splits, not painted except top/bottom 18" for visibility,)	Pass ( )	Fail ( )	N/A ( )

Inspected by: _____

* **Damages**: _____

* All damaged ladders must be removed from service and tagged :

"OUT OF SERVICE-DO NOT USE"

* **Repaired by**: _____